

- Invasive species identified in the soil placement area will be eradicated in accordance with The CVRD strategy for invasive plant management (CVRD, 2019b).

## **6 Groundwater Impact Assessment**

The application area is within 100 m of Aquifer 203 and approximately 100 m from Aquifer 208, both high vulnerability. As requested by the CVRD, a Ground Water Impact Assessment was prepared by a Registered Professional. The assessment is provided in Appendix 4. The assessment concluded that the soil deposit activity would not pose a threat to the local aquifer quality or quantity.

## **7 Site Remediation**

The following subsections describe the remediation plans that will occur subsequent to completion of the soil deposit activities.

### **7.1 Landscaping**

Consistent with the proposed equestrian use, the following landscaping measures are planned:

1. Level grades will be finished with a layer of crushed rock and/or a layer of mulch. These are porous materials that will promote diffuse drainage, and will cover deposited soils to mitigate erosion. Some areas will also be strategically landscaped with vegetation to promote soil stabilization and aesthetic interest.
2. Slopes will be vegetated with a combination of seed (e.g. native grasses, wildflowers), trees, and/or shrubs. This will promote slope stabilization, and erosion protection. Appropriate native seed/plant/tree species will be used where practical for re-vegetation and landscaping.

### **7.2 Stormwater Management**

Stormwater will be managed using the following principles, so as not to create erosion or other adverse effects of the landscape:

- Natural drainage patterns on the property will be retained where feasible.
- Land areas will be sloped to collection ditches/swales, settling ponds, and natural vegetated areas to minimize sediment transport and turbidity.
- The majority of land surface will be landscaped with permeable materials to allow for diffuse infiltration into the ground.
- Bare soils on sloped surfaces will be vegetated to slow runoff and mitigate erosion.

### **7.3 Noxious Weeds and Invasive Species**

Site remediation will be completed in a manner that will minimize colonization and spread of noxious weeds. As stated in Section 5.7, the most significant invasive plant species documented in the CVRD include Scotch broom, Canada Thistle, Himalayan Blackberry, St. Johns' Wort, Oxeye Daisy, Bull Thistle, Common Tansy, Japanese knotweed, Yellow Iris, Tansey Ragwort and Curled Dock (Cowichan Valley

March 19, 2020  
LHC File: 2004

Great Pacific Consulting Ltd.  
202 - 2780 Veterans Memorial Parkway  
Victoria, BC  
V9B 3S6

Attention: Jason Clarke, P. Eng.

Re: Groundwater Impact of Soil Filling at PID 027-514-382, 670 Stebbings Road, Shawnigan Lake, B.C.

Following our e-mails January 2020 and follow-up communications we have assessed the potential impacts from soil deposition on the above described property. Our findings are presented in the following sections.

The Cowichan Valley Regional District (CVRD) has developed a bylaw to manage the deposit of soils within the region. The Bylaw (No. 4236) has established a permitting process for the deposit of soil and is intended to protect streams, groundwater resources and other sensitive features. The bylaw guards against the unauthorized importation of contaminated soils. Sites receiving more than 1000 m<sup>3</sup>/year require a Type "C" permit.

This report is designed to assess the risk to the groundwater resource from the deposit of soils on the subject property. The report will form part of the application package for the Type "C" permit. See a property location Plan in Figure 1.

## **1.0 PHYSICAL SETTING**

### **1.1 Climate**

The Shawnigan Lake region is within the West Coast Temperature Zone, with an average annual precipitation of 1,247.6 mm, of which 75.5 cm falls as snow. The rainy season is generally between October to March, where precipitation averages greater than 100 mm per month. The coldest months are typically from December to February where daytime highs are lower than 5 degrees C. From June to September daytime temperatures are typically in the 15 degrees C range.


### **1.2 Topography and Surface Water Drainage**

The subject property is located on moderately to steeply sloping terrains, with slopes ranging from 9 - 30%. The topography is complex, with multiple direction slopes and irregular surfaces. The topography slopes down to the North or toward Van Horne Creek. Surface and sub-surface drainage follow this direction.

### **1.3 Soils**

The main native soils found on the subject property are the Shawnigan Moraine and the Rosewall Colluvium soil units, consisting of gravelly sandy loam, which is well drained. The Shawnigan unit is derived from glacial deposition and the Rosewall unit from weathering of bedrock. Considering the nature of the soils, a horizontal hydraulic conductivity Kh of 2 - 5 m/day can be estimated. Soil layer thickness or bedrock depth is variable in the region, with depths up to 37.5 m.

Figure 1 - Location Plan



## 1.4 Geology

The study area is blanketed by glacial drift and colluvium deposits. Drilling records indicate permeable sand and gravel layers (colluvium soils) overly till which in-turn overlies bedrock. The Geological Survey of Canada Map 1553A by J.E.Muller (1980) shows the area of study is underlain by the Wark Gneiss rock unit. The rock unit is extensively folded and faulted. There are major faults to the north in this unit but none in the immediate vicinity of the subject property. This rock unit consists of metamorphosed volcanics and is generally favourable for domestic or community water supply development. Moderate yields can be obtained from these rocks (1 to 50 USgpm).

## 1.5 Hydrogeology

The on-site well record (Well ID #25649) indicates an unconsolidated sand/gravel type aquifer can be found beneath the area of soil filling. This aquifer is small and localized, and it is not mapped. However, the sand/gravel layer here extends down to 10.67 m (35 feet) and is capable of supplying 0.63 L/s (10 USgpm). The site well plus nearby well records are attached as Attachment #1. The sand and gravel aquifer overlies a till layer. Beneath the till layer lies bedrock. The sand gravel aquifer has an estimated hydraulic conductivity of 2-5 m<sup>2</sup>/d.

Principally due to fractures, in addition to probable bedding plane and geologic contact zones, the bedrock is saturated at depth and the water bearing zones (aquifers) are replenished through the vertical infiltration of precipitation and/or by lateral flow from up-slope recharge zones. The local bedrock wells are generally greater than 30 m deep and completed in the Wark Gneiss bedrock unit.


The regional topography indicates the groundwater flow direction to be toward the north in the surficial and bedrock aquifers. The bedrock aquifer has a hydraulic conductivity ranging from 0.00001 to 0.10 m/d. (Domenico & Schwartz, 1990). A recharge rate to the bedrock aquifer of 10 percent of precipitation, or 0.10 x 1,247 mm/year = 125 mm/year, has been estimated by LHC based on these rock conductivities and the characteristics of the overlying soils. The mapped bedrock aquifer beneath the site is Aquifer No. 203. See a Summary of Aquifer data in Figure 2.

## 2.0 IMPACT OF SOIL DEPOSITION ON AQUIFER #203

A portion (about 1/8) of the subject property will be subject to soil filling. The purpose of the soil and rock fill being placed on the subject property is to re-shape the landscape making the site usable as a horse-riding facility. This filling plan will not negatively impact the underlying aquifers. The following reasons can be cited for this conclusion:

- Only clean fill soil is being deposited at the site. All soil suppliers must fill-in and sign a "Soil/Material Acceptance Agreement". This ensures that only clean (uncontaminated) soils are received. See Attachment #2.
- Soils being deposited are primarily from Victoria region residential and commercial developments. Soils are mainly native soil that has been excavated to facilitate construction.
- A small amount of rock and concrete is received and is being used for on-site road construction or stabilization.
- Original site drainage features are being maintained and silt traps and ponds are used to ensure clean/clear runoff from active areas.
- All creeks and ponds, inspected on March 4, 2020, exhibited clean/clear water. The Van Horne Creek appears pristine.
- A minimum 30 m buffer is maintained around the natural water features on the property.


Figure 2 - Summary of Aquifer



**Aquifer Description (Mapping Report):**  
Fractured crystalline (igneous intrusive or metamorphic, meta-sedimentary, meta-volcanic, volcanic) rock aquifer (subtype = 6b).

Aquifer Details	
Region	West Coast
Water District	Victoria
Aquifer Area	31 km <sup>2</sup>
No. Wells Correlated to Aquifer	172
Vulnerability to Contamination	High
Productivity	Low
Aquifer Classification	IIA
Hydraulic Connectivity <sup>1</sup>	Not Likely
Aquifer Stress Index	Less stressed
No. Water Licences Issued to Wells	0
Observation Wells (Active, Inactive)	None

<sup>1</sup> Based on broad regional assessment



**Disclaimer:**

Use of information from Aquifer factsheets (accessed by BC government website) is subject to limitation of liability provisions (further described on that web site). That information is provided by the BC government as a public service or an "as is" basis, without warranty of any kind, whether express or implied, and its use is at your own risk. Under no circumstances will the BC government, or its staff, agents and contractors, be responsible or liable to any person or business entity, for any direct, indirect, special, incidental, consequential or any other loss or damages to any person or business entity based on this factsheet or any use of information from it.

Detailed methods for all figures are described in the companion document (Aquifer Factsheet - Companion Document.pdf).

Factsheet generated: 2019-03-06. Available from: [https://s3.ca-central-1.amazonaws.com/aquifer-docs/0000/00203\\_Aquifer\\_Factsheet.pdf](https://s3.ca-central-1.amazonaws.com/aquifer-docs/0000/00203_Aquifer_Factsheet.pdf).

- The underlying bedrock aquifer #203 is protected by overlying sand/gravel and till layers.
- All equipment on-site is maintained in good order and leaks (hydraulic fluids) are fixed and cleaned up immediately.
- In general Aquifer #203 is classified as Highly Vulnerable, however, a site-specific assessment using local well data (Attachment #1 - Well Records) indicates Aquifer #203 has a low vulnerability at this site. See Attachment #3 for the vulnerability calculation.
- Overall, the site is well managed, clean and neat. Best management practices are being employed.
- In general filling soil over a rock aquifer is beneficial to recharge. The soil acts as a "sponge" soaking up wet season precipitation and slowly releasing it to the underlying rock fractures. Filled soil with about 30% porosity can store much more water than fractured rocks with less than 10% porosity.

### 3.0 CONCLUSION

1. Assuming current operating plans and procedures are maintained we do not consider the soil deposition on the subject property a threat to local aquifer water quality or quantity.
2. The subject site (PID 027-514-382) can be granted a Type "C" Soil Deposit Permit from the CVRD.

### 4.0 CLOSURE / DISCLAIMER

This report has been prepared in accordance with generally accepted groundwater engineering practices. The opinions expressed herein are considered valid at the time of writing. Changes in site conditions can occur, however, whether due to natural events (e.g. climate change, earthquakes) or to human activities (e.g. recharge area modification or blasting on this or adjacent properties). In addition, changes in regulations and standards may occur, whether they result from legislation or the broadening of knowledge. This report is therefore subject to review and revision as changed conditions are identified.


In formulating our analysis, we have relied on information provided by others; well drillers, surveyors and hydrogeology reports/aquifer mapping. The information provided by others is believed to be accurate but cannot be guaranteed by Lowen Hydrogeology Consulting Ltd.

Furthermore, if the recommendations in this report are not implemented, the undersigned assumes no responsibility for any adverse consequences that may occur.

Respectfully submitted,

Yours very truly,

LOWEN HYDROGEOLOGY CONSULTING LTD.



Dennis Lowen, P. Eng., P. Geo.

DL/hr



March 19, 2020



## References

1. Cowichan Valley Regional District (CVRD) The Bylaw (No. 4236)
2. Domenico & Schwartz, 1990; *Physical and Chemical Hydrogeology*
3. J. E. Muller, 1980, *The Geological Survey of Canada Map 1553A*
4. Lawrence, R. W., Feb. 2018; *Admirals-Mackenzie Interchange Project - Evaluation of Geotechnical Characteristics of Aggregates for Roadbed Construction*. Tech-Mem. 18-05

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Log Report WTN 95488



### Groundwater Wells and Aquifers

#### Well Summary

Well Tag Number: 95488  
Well Identification Plate Number: 25649  
Owner Name: ISLAND TIMBERLANDS GROUP LTD  
Intended Water Use: Private Domestic

Well Status: New  
Well Class: Water Supply  
Well Subclass: Domestic  
Aquifer Number: 1143

Observation Well Number:  
Observation Well Status:  
Environmental Monitoring System (EMS) ID:  
Alternative specs submitted: No

#### Licensing Information

Licensed Status: Unlicensed

Licence Number:


#### Location Information

Street Address: STEBBINGS ROAD  
Town/City: MALAHAT

#### Legal Description:

Lot	6
Plan	
District Lot	50
Block	
Section	
Township	
Range	
Land District	29
Property Identification Description (PID)	009355600

Description of Well Location: PROPOSED SUBDIVISION



#### Geographic Coordinates - North American Datum of 1983 (NAD 83)

Latitude: 48.562874 Longitude: -123.599659  
UTM Easting: 455757 UTM Northing: 5379038  
Zone: 10 Coordinate Acquisition Code: (10 m accuracy) Handheld GPS with accuracy of +/- 10 metres

#### Well Activity

Activity	Work Start Date	Work End Date	Drilling Company	Date Entered
There has been no activity related to this well.				

<https://apps.nrs.gov.bc.ca/gwells/well/95488>

#### Comments

No comments submitted

Alternative Specs Submitted: No

#### Documents

No additional documentation available for this well.

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Work Dates

Start Date of Construction	End Date of Construction	Start Date of Alteration	End Date of Alteration	Start Date of Decommission	End Date of Decommission
2008-03-10	2008-03-11				

## Well Completion Data

Total Depth Drilled: 36.00 feet  
Finished Well Depth: 34.00 feet  
Final Casing Stick Up: 30.000 inches  
Depth to Bedrock:  
Ground elevation: 905.00

Static Water Level (BTOC): 5.00 feet  
Estimated Well Yield: 10.000 USGPM  
Artesian Flow:  
Artesian Pressure:  
Method of determining elevation: GPS

Well Cap: STEEL  
Well Disinfected Status: Disinfected  
Drilling Method:  
Orientation of Well: VERTICAL

## Lithology

From (ft bgl)	To (ft bgl)	Raw Data	Description	Moisture	Colour	Hardness	Observations	Water Bearing Flow Estimate (USGPM)
0.00	35.00		coarse		brown	Loose	SOME SAND	10.0000
35.00	36.00		silty		brown	Hard	FINE, DENSE. SEALED WATER OFF.	

## Casing Details

From (ft)	To (ft)	Casing Type	Casing Material	Diameter	Wall Thickness	Drive Shoe
0.00	18.00	Steel Removed		9.000		Not Installed
0.00	34.00		Steel	6.000	0.219	Installed

## Surface Seal and Backfill Details

Surface Seal Material: Bentonite clay  
Surface Seal Installation Method: Poured  
Surface Seal Thickness: 1.50  
Surface Seal Depth:

Backfill Material Above Surface Seal:  
Backfill Depth:

## Liner Details

Liner Material:  
Liner Diameter:  
Liner from:

Liner Thickness:  
Liner to:

Liner perforations  
From

To

There are no records to show

## Screen Details

Intake Method: Open

Bottom

Type:

Material:

Opening:

Bottom:

Installed Screens

From

To

Diameter

Assembly Type

Slot Size

There are no records to show

## Well Development

Developed by:

Development Total Duration: 1.00 hours

## Well Yield

Estimation Method: AIR\_LIFT  
Static Water Level Before Test:  
Hydrofracturing Performed: No

Estimation Rate: 10.00  
Drawdown:  
Increase in Yield Due to Hydrofracturing:

Estimation Duration: 1.00

## Well Decommission Information

Reason for Decommission:  
Sealant Material:  
Decommission Details:

Method of Decommission:  
Backfill Material:

## Disclaimer

The information provided should not be used as a basis for making financial or any other commitments. The Government of British Columbia accepts no liability for the accuracy, availability, suitability, reliability, usability, completeness or timeliness of the data or graphical depictions rendered from the data.

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Log Report WTN 106005



### Groundwater Wells and Aquifers

#### Well Summary

Well Tag Number: 106005  
Well Identification Plate Number: 35854  
Owner Name: DON MANN EXCAVATION  
Intended Water Use: Private Domestic

Well Status: New  
Well Class: Water Supply  
Well Subclass: Domestic  
Aquifer Number: 203

Observation Well Number:  
Observation Well Status:  
Environmental Monitoring System (EMS) ID:  
Alternative specs submitted: No

#### Licensing Information

Licensed Status: Unlicensed

Licence Number:

#### Location Information


Street Address:

Town/City:

Legal Description:

Lot	6(A)
Plan	VIP85007
District Lot	50
Block	
Section	
Township	
Range	
Land District	29
Property Identification Description (PID)	

Description of Well Location: NONE PROVIDED



Geographic Coordinates - North American Datum of 1983 (NAD 83)

Latitude: 48.568547

Longitude: -123.603847

UTM Easting: 455453

UTM Northing: 5379671

Zone: 10

Coordinate Acquisition Code: (10 m accuracy) Handheld GPS with accuracy of +/- 10 metres

#### Well Activity

Activity	Work Start Date	Work End Date	Drilling Company	Date Entered
----------	-----------------	---------------	------------------	--------------

There has been no activity related to this well.

#### Disclaimer

The information provided should not be used as a basis for making financial or any other commitments. The Government of British Columbia accepts no liability for the accuracy, availability, suitability, reliability, usability, completeness or timeliness of the data or graphical depictions rendered from the data.

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Work Dates

Start Date of Construction	End Date of Construction	Start Date of Alteration	End Date of Alteration	Start Date of Decommission	End Date of Decommission
2011-04-14	2011-04-18				

## Well Completion Data

Total Depth Drilled: 280.00 feet  
Finished Well Depth: 200.00 feet  
Final Casing Stick Up: 30.000 inches  
Depth to Bedrock: 25.00 feet  
Ground elevation: 787.00

Static Water Level (BTOC):  
Estimated Well Yield:  
Artesian Flow:  
Artesian Pressure:  
Method of determining elevation: Unknown

Well Cap:  
Well Disinfected Status: Not Disinfected  
Drilling Method: Air Rotary  
Orientation of Well: VERTICAL

## Lithology

From (ft bgl)	To (ft bgl)	Raw Data	Description	Moisture	Colour	Hardness	Observations	Water Bearing Flow Estimate (USGPM)
0.00	20.00							
20.00	25.00	HARD PAN CASING SET BEDROCK						
25.00	100.00					Soft		
100.00	200.00	SOME QUARTZ						
200.00	280.00					Soft	FRACTURE 260' 3 GAL	

## Casing Details

From (ft)	To (ft)	Casing Type	Casing Material	Diameter	Wall Thickness	Drive Shoe
0.00	25.00		Steel	6.630	0.219	Installed

## Surface Seal and Backfill Details

Surface Seal Material: Bentonite clay  
Surface Seal Installation Method:  
Surface Seal Thickness:  
Surface Seal Depth:

Backfill Material Above Surface Seal:  
Backfill Depth:

## Liner Details

Liner Material: PVC  
Liner Diameter:  
Liner from:

Liner Thickness:  
Liner to:

Liner perforations  
From To  
50.00 ft 90.00 ft

## Screen Details

Intake Method:  
Type:  
Material:  
Opening:  
Bottom:

Installed Screens  
From To Diameter Assembly Type Slot Size  
There are no records to show

## Well Development

Developed by:

Development Total Duration: 2.00 hours

## Well Yield

Estimation Method: AIR\_LIFT  
Static Water Level Before Test:  
Hydrofracturing Performed: No

Estimation Rate: 3.00  
Drawdown:  
Increase in Yield Due to Hydrofracturing:

Estimation Duration: 2.00

## Well Decommission Information

Reason for Decommission:  
Sealant Material:  
Decommission Details:  
Comments

Method of Decommission:  
Backfill Material:

No comments submitted

Alternative Specs Submitted: No

## Documents

- WTN 106005\_Well Construction.pdf

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Log Report WTN 52475



### Groundwater Wells and Aquifers

#### Well Summary

Well Tag Number: 52475  
Well Identification Plate Number:  
Owner Name: FRED KING  
Intended Water Use: Private Domestic

Well Status: New  
Well Class: Unknown  
Well Subclass:  
Aquifer Number: 203

Observation Well Number:  
Observation Well Status:  
Environmental Monitoring System (EMS) ID:  
Alternative specs submitted: No

#### Licensing Information

Licensed Status: Unlicensed

Licence Number:


#### Location Information

Street Address: SHAWNIGAN LK RD  
Town/City:

#### Legal Description:

Lot	A
Plan	28099
District Lot	50
Block	
Section	
Township	
Range	
Land District	29
Property Identification Description (PID)	

Description of Well Location:



Leaflet | Powered by Esri | Government of British Columbia, DataBC, GeoBC

Geographic Coordinates - North American Datum of 1983 (NAD 83)

Latitude: 48.567198

Longitude: -123.600361

UTM Easting: 455709

UTM Northing: 5379519

Zone: 10

Coordinate Acquisition Code: (50 m accuracy) Digitized from 1:20,000 mapping

#### Well Activity

Activity	Work Start Date	Work End Date	Drilling Company	Date Entered
Legacy record	1983-07-16		A. D. Baker Drilling	August 13th 2003 at 3:46 AM

#### Well Work Dates

Start Date of Construction	End Date of Construction	Start Date of Alteration	End Date of Alteration	Start Date of Decommission	End Date of Decommission
1983-07-16					

#### Comments

RATE: 1.5 GPM. METHOD OF DRILLING = DRILLED

Alternative Specs Submitted: No

#### Documents

No additional documentation available for this well.

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Completion Data

Total Depth Drilled:  
Finished Well Depth: 300.00 feet  
Final Casing Stick Up:  
Depth to Bedrock: 7.00 feet  
Ground elevation:

Static Water Level (BTOC):  
Estimated Well Yield: 1.500 USGPM  
Artesian Flow:  
Artesian Pressure:  
Method of determining elevation: Unknown

Well Cap:  
Well Disinfected Status: Not Disinfected  
Drilling Method: Other  
Orientation of Well: VERTICAL

## Lithology

From (ft bgl)	To (ft bgl)	Raw Data	Description	Moisture	Colour	Hardness	Observations	Water Bearing Flow Estimate (USGPM)
0.00	0.00	Casing set (through large boulder) 2'						
0.00	0.00	into rock						
0.00	3.00	Gravel						
3.00	6.00	Boulder						
6.00	7.00	Gravel						
7.00	198.00	Granite						
198.00	0.00	1.5 GPM						
198.00	300.00	Granite						

## Casing Details

From (ft)	To (ft)	Casing Type	Casing Material	Diameter	Wall Thickness	Drive Shoe
There are no records to show						

## Surface Seal and Backfill Details

Surface Seal Material: Other  
Surface Seal Installation Method:  
Surface Seal Thickness:  
Surface Seal Depth:

Backfill Material Above Surface Seal:  
Backfill Depth:

## Liner Details

Liner Material:  
Liner Diameter:  
Liner from:

Liner Thickness:  
Liner to:

Liner perforations  
From To  
There are no records to show

## Screen Details

Intake Method:  
Type:  
Material: Other  
Opening:  
Bottom:

Installed Screens					Slot Size
From	To	Diameter	Assembly Type		
There are no records to show					

## Well Development

Developed by:  
Well Yield

Development Total Duration:

Estimation Method:  
Static Water Level Before Test:  
Hydrofracturing Performed: No

Estimation Rate:  
Drawdown:  
Increase in Yield Due to Hydrofracturing:  
Estimation Duration:

## Well Decommission Information

Reason for Decommission:  
Sealant Material:  
Decommission Details:

Method of Decommission:  
Backfill Material:

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Log Report WTN 96127



### Groundwater Wells and Aquifers

#### Well Summary

Well Tag Number: 96127  
Well Identification Plate Number: 25650  
Owner Name: ISLAND TIMBERLANDS GP LTD  
Intended Water Use: Private Domestic

Well Status: New  
Well Class: Water Supply  
Well Subclass: Domestic  
Aquifer Number: 203

Observation Well Number:  
Observation Well Status:  
Environmental Monitoring System (EMS) ID:  
Alternative specs submitted: No

#### Licensing Information

Licensed Status: Unlicensed

Licence Number:


#### Location Information

Street Address: STEBBINGS ROAD  
Town/City: MALAHAT

#### Legal Description:

Lot	7
Plan	
District Lot	50
Block	
Section	
Township	
Range	
Land District	29
Property Identification Description (PID)	009355600

Description of Well Location: PROPOSED SUBDIVISION



Geographic Coordinates - North American Datum of 1983 (NAD 83)

Latitude: 48.564334  
UTM Easting: 455916  
Zone: 10

Longitude: -123.597521  
UTM Northing: 5379199  
Coordinate Acquisition Code: (10 m accuracy) Handheld GPS with accuracy of +/- 10 metres

#### Well Activity

Activity	Work Start Date	Work End Date	Drilling Company	Date Entered
----------	-----------------	---------------	------------------	--------------

There has been no activity related to this well.

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Work Dates

Start Date of Construction	End Date of Construction	Start Date of Alteration	End Date of Alteration	Start Date of Decommission	End Date of Decommission
2008-03-12	2008-03-13				

## Well Completion Data

Total Depth Drilled: 205.00 feet  
Finished Well Depth: 205.00 feet  
Final Casing Stick Up: 30.000 inches  
Depth to Bedrock: 70.00 feet  
Ground elevation: 879.00

Static Water Level (BTOC): 45.00 feet  
Estimated Well Yield: 5.000 USGPM  
Artesian Flow:  
Artesian Pressure:  
Method of determining elevation: GPS

Well Cap: STEEL  
Well Disinfected Status: Disinfected  
Drilling Method: Air Rotary  
Orientation of Well: VERTICAL

## Lithology

From (ft bgl)	To (ft bgl)	Raw Data	Description	Moisture	Colour	Hardness	Observations	Water Bearing Flow Estimate (USGPM)
0.00	18.00	TILL BOULDERS			grey	Hard		
18.00	24.00				grey	Hard	VERY ROUGH	
24.00	32.00	BOULDER			green	Hard	DRILLED WITH ODEX	
32.00	37.00				grey	Hard		
37.00	70.00				brown	Hard		
70.00	80.00	WEATHERED BEDROCK			brown	Medium		
80.00	205.00				green	Medium	5.5 HOLE. 170' - 3 GPM; 205' - 5 GPM.	

## Casing Details

From (ft)	To (ft)	Casing Type	Casing Material	Diameter	Wall Thickness	Drive Shoe
0.00	18.00	Steel Removed		9.000		Not Installed
0.00	80.00		Steel	6.000	0.219	Installed
80.00	205.00		Open hole	5.500		Not Installed

## Surface Seal and Backfill Details

Surface Seal Material: Bentonite clay  
Surface Seal Installation Method: Poured  
Surface Seal Thickness: 15.00  
Surface Seal Depth:

Backfill Material Above Surface Seal:  
Backfill Depth:

## Liner Details

Liner Material:  
Liner Diameter:  
Liner from:

Liner Thickness:  
Liner to:

Liner perforations  
From

To

There are no records to show

## Screen Details

Intake Method: Open Bottom  
Type:  
Material:  
Opening:  
Bottom:

### Installed Screens

From	To	Diameter	Assembly Type	Slot Size
There are no records to show				

## Well Development

Developed by:  
Well Yield

Development Total Duration: 1.00 hours

Estimation Method: AIR\_LIFT  
Static Water Level Before Test:  
Hydrofracturing Performed: No

Estimation Rate: 5.00  
Drawdown:  
Increase in Yield Due to Hydrofracturing:

Estimation Duration: 1.00

## Well Decommission Information

Reason for Decommission:  
Sealant Material:  
Decommission Details:

Method of Decommission:  
Backfill Material:

## Comments

METHOD OF DRILLING AIR ROTARY & ODEX.  
Alternative Specs Submitted: No

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Log Report WTN 96092



### Groundwater Wells and Aquifers

#### Well Summary

Well Tag Number: 96092  
Well Identification Plate Number: 25646  
Owner Name: ISLAND TIMBERLANDS GP LTD  
Intended Water Use: Private Domestic

Well Status: New  
Well Class: Water Supply  
Well Subclass: Domestic  
Aquifer Number: 1143

Observation Well Number:  
Observation Well Status:  
Environmental Monitoring System (EMS) ID:  
Alternative specs submitted: No

#### Licensing Information

Licensed Status: Unlicensed

Licence Number:


#### Location Information

Street Address: STEBBINGS ROAD  
Town/City: MALAHAT

#### Legal Description:

Lot	3
Plan	PROPOSED SUBDIVISION
District Lot	50
Block	
Section	
Township	
Range	
Land District	29
Property Identification Description (PID)	009355600

Description of Well Location: NOT PROVIDED



#### Geographic Coordinates - North American Datum of 1983 (NAD 83)

Latitude: 48.562865	Longitude: -123.599618
UTM Easting: 455760	UTM Northing: 5379037
Zone: 10	Coordinate Acquisition Code: (10 m accuracy) Handheld GPS with accuracy of +/- 10 metres

#### Well Activity

Activity	Work Start Date	Work End Date	Drilling Company	Date Entered
There has been no activity related to this well.				

# Attachment 1

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Work Dates

Start Date of Construction	End Date of Construction	Start Date of Alteration	End Date of Alteration	Start Date of Decommission	End Date of Decommission
2008-02-21	2008-02-27				

## Well Completion Data

Total Depth Drilled: 147.00 feet  
Finished Well Depth: 120.00 feet  
Final Casing Stick Up: 36.000 inches  
Depth to Bedrock:  
Ground elevation: 1012.00

Static Water Level (BTOC): 99.00 feet  
Estimated Well Yield: 3.000 USGPM  
Artesian Flow:  
Artesian Pressure:  
Method of determining elevation: GPS

Well Cap: STEEL  
Well Disinfected Status: Disinfected  
Drilling Method: Air Rotary  
Orientation of Well: VERTICAL

## Lithology

From (ft bgl)	To (ft bgl)	Raw Data	Description	Moisture	Colour	Hardness	Observations	Water Bearing Flow Estimate (USGPM)
0.00	25.00	TILL COBBLES			brown	Hard		
25.00	50.00	TILL COBBLES BOULDERS			grey	Hard	VERY ROUGH	
50.00	70.00				brown	Medium		
70.00	78.00	TILL COBBLES			brown	Hard		
78.00	105.00				brown	Medium		
105.00	111.00				brown	Hard		
111.00	121.00		medium		brown	Loose	WET	
121.00	123.00	TILL CLAY			brown	Hard		
123.00	129.00				grey	Hard	CASING STOPPED	
129.00	147.00				grey	Hard		

## Casing Details

From (ft)	To (ft)	Casing Type	Casing Material	Diameter	Wall Thickness	Drive Shoe
0.00	8.00	Steel Removed		9.000		Not Installed
0.00	115.00		Steel	6.000	0.219	Installed

## Surface Seal and Backfill Details

Surface Seal Material: Bentonite clay  
Surface Seal Installation Method: Poured  
Surface Seal Thickness: 1.50  
Surface Seal Depth:

Backfill Material Above Surface Seal:  
Backfill Depth:

## Liner Details

Liner Material:  
Liner Diameter:  
Liner from:

Liner Thickness:  
Liner to:

Liner perforations  
From To

There are no records to show

## Screen Details

Intake Method: Screen  
Type: Pipe size  
Material: Stainless Steel  
Opening: Continuous Slot  
Bottom: Other

### Installed Screens

From	To	Diameter	Assembly Type	Slot Size
114.00 ft	116.00 ft	6.00	K_RISER	
116.00 ft	120.00 ft	6.00	SCREEN	15.00

# Attachment 1

---

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Well Development

Developed by:

Development Total Duration: 3.00 hours

## Well Yield

Estimation Method: BAILING

Estimation Rate: 3.00

Estimation Duration: 3.00

Static Water Level Before Test:

Drawdown:

Hydrofracturing Performed: No

Increase in Yield Due to Hydrofracturing:

## Well Decommission Information

Reason for Decommission:

Method of Decommission:

Sealant Material:

Backfill Material:

Decommission Details:

## Comments

SCREEN BOTTOM THREADED. CUTE SHOE BACKFILL. SET SCREEN AT 120 FEET.

Alternative Specs Submitted: No

## Documents

- WTN 96092\_Well Construction.pdf

## Disclaimer

The information provided should not be used as a basis for making financial or any other commitments. The Government of British Columbia accepts no liability for the accuracy, availability, suitability, reliability, usability, completeness or timeliness of the data or graphical depictions rendered from the data.

---

## Soil/Material Acceptance Agreement



### Soil/Material Acceptance Agreement

This Agreement must be executed before any soil/material can be accepted by Mike Ferguson's Affordable Services Inc. (DBA): ASI Contracting. The ASI Contracting Site located at 670 Stebbings Road, Shawnigan Lake, B.C. requires this Agreement to be executed by an authorized signatory of your Company.

By signing this Agreement, the Company represents and warrants to ASI that none of the soil/material delivered to ASI by the Company contains any contaminants at concentrations exceeding the limits listed in Column II of Schedule 7 of the Contaminated Sited Regulation (CSR), B.C. Reg 375/96 or contaminants listed under the Special Waste Regulation, B.C. Reg. 63/88 or any other criteria stipulated by ASI, and which may be amended by ASI from time to time at its sole discretion upon notice to the Company (soil material not exceeding such limits as may be amended is referred to herein as "Clean Soil")

ASI further reserves the right to inspect and sample and/or may require the Company to sample any and all soil/material before accepting the soil/material. The right of ASI to inspect or sample the material does not reduce, restrict or otherwise affect the Company's liability in relation to soil/material that is not Clean Soil. Any soil/material that is not Clean Soil may be rejected by ASI acting in its sole discretion and ASI may request the company to remove and dispose of such soil/material. Such removal and disposal being at the sole cost, risk and responsibility of the Company. If after acceptance by ASI, the soil/material is discovered not to be Clean Soil, ASI will notify the Company. If requested, the Company shall remove the soil/material within 24 hours of notification and dispose of the same in accordance with all applicable laws.

The Company agrees to defend, indemnify and hold ASI harmless from and against any and all claims, demands, orders, causes of action, damages, liabilities, losses, expenses, penalties, and all costs of defense relative thereto, including legal fees caused by or resulting from the Company's breach of this Agreement, including without limitation, any breach of the Company's obligation to deliver only Clean Soil.

This Agreement does not confer a right on the Company to deliver soil/material to the ASI Site. ASI reserves the right to reject for any reason, any and all deliveries of soil/material made by or desired to be made by, the Company.

This Agreement commences effective as of the first day on which the Company delivers soil/material to the ASI Site.

Any waiver of any provision of this Agreement must be in writing signed by ASI Contracting.

Name:	Title:
Company:	Company Address:
Site Name: ASI Contracting Fill Site	Site Address: 670 Stebbings Road, Shawnigan Lake B.C.
Signature:	Today's Date:

ASI Contracting. 670 Stebbings Road Shawnigan Lake, B.C. Office (250) 590-3867. Direct (250) 889-9353.

# Attachment 3

Groundwater Impact of Soil Filling  
670 Stebbings Road, Shawnigan Lake, B.C.

## Aquifer #203 - Vulnerability to Contamination from Surface Sources

### AQUIFER VULNERABILITY INDEX CALCULATIONS\*

PROJECT: Stebbings Road Soil Fill Impact Assessment  
PROJECT No.: 2004  
DATE: 19/03/2020  
WELL ID. PLATE No.: 25649  
WELL TAG No.: 95488  
LOCATION: Stebbings Road , PID 027-514-384

Overlying layers			
Layer	Thickness (m)	K value (m/d)	c** (years)
Sand/gravel	2.13	5	1.17E-03
Till, clay, silt	16.5	0.00001	4.52E+03
(average 4 wells)			

TOTAL **4,521** years  
Low Vulnerability

\* Van Stempvoort, D., Ph.D., Ewart, L., and L. Wassener, 1992. AVI: A Method for Groundwater Protection Mapping in the Prairie Provinces of Canada, Prairie Provinces Water Board, Regina, Sask.

\*\* Hydraulic Resistance "c"

Hydraulic Resistance,  $c = \sum d_i / K_i$ , for layers 1 to i

The lower the hydraulic resistance (c) the higher the vulnerability:

c = Less than 10 years - extremely high vulnerability

c = 10 - 100 years - high vulnerability

c = 100 - 1000 years - moderate vulnerability

c = 1000 - 10,000 - low vulnerability

c = greater than 10,000 - extremely low vulnerability